

Description: Fabric supported fully coated natural rubber gauntlet with smooth palm

- Features & Benefits:
- * Two piece liner without seams in the working area eliminates hand irritation
 - * Anatomically shaped to provide good fit
 - * Bacteriostatic and fungistatic additives
 - * Compliant with (EC) No. 1935/2004 & EU 10/2011 (Blue)
 - * Cotton / Kevlar combination gives a better cut resistance and extra comfort
 - * Cotton interlock liner absorbs perspiration and adds to comfort
 - * Durable and washable
 - * Extended gauntlet cuff to protect forearm
 - * Fully coated for extra protection
 - * Ingredients comply with FDA regulations for food contact (Blue only)
 - * Liquid proof for use in wet conditions
 - * Safe for food handling



Applications: Logistics and warehousing, Facility maintenance

Elastomer: Natural rubber
 Thickness: 1.25 +/- 0.10 mm
 Lining: Interlock
 Former: Plain CIII
 Exterior: Finished smooth
 Cuff Types: Gauntlet
 Treatments:
 Colours: Blue B7


CE Certification: Conforms to PPE Regulation EU 2016/425 to(Complex Design) Personal Protective Equipment after assessment against standards EN 374-1:2016+A1:2018, EN 388:2016+A1:2018 ,EN 374-5 : 2016, EN ISO 21420:2020 and EN 407 : 2020

Conforms to: ASTM D4679 of 2002

| Physical Dimensions: | Size | Palm | Wrist | Cuff | Length |
|----------------------|-------------|------|-------|------|--------|
| | 6 | 208 | 216 | 274 | 300 |
| | 7.5 (M) | 222 | 228 | 288 | 300 |
| | 8.5 (L) | 234 | 240 | 296 | 300 |
| | 9 (L+) | 242 | 254 | 304 | 300 |
| | 10 (XL+) | 252 | 268 | 308 | 300 |
| | 11.5 (XXXL) | 264 | 272 | 310 | 300 |

Circumference in mm, +/- 5 mm Tol. +/- 10 mm

EN 374-4

| Protection against Chemical hazards | Performance | Degradation % |
|---|----------------------------|---------------|
| EN ISO 374-1/TYPE A | | |
|  | * Methanol (A) | Level 2 |
| | * Sodium hydroxide 40% (K) | Level 6 |
| | * Sulphuric acid 96% (L) | Level 4 |
| | * Nitric acid 65% (M) | Level 6 |
| | * Acetic acid 99% (N) | Level 3 |
| | | 17.9 |
| | | -5.8 |
| | | 35 |
| | | 5.5 |
| | | 30.9 |

Note: Printed copies are valid only on the date printed

Printed Date: 01-Dec-2022

Revision:4

Published Date: 16-Nov-2022

DPL
Handling you with care

No: 400, Deans Road, Colombo 10, Sri Lanka

Phone: +94-0122-683-964

Fax: +94-0122-699-018

E-Mail: postmast@dplgroup.com

| | | |
|-----------------------------|---------|------|
| * Hydrogen peroxide 30% (P) | Level 6 | -2.8 |
| * Formaldehyde 37% (T) | Level 6 | 12.1 |
| * Hydrofluoric acid 40% (S) | Level 6 | X |

| Protection against Mechanical hazards | Performance |
|---------------------------------------|-------------|
|---------------------------------------|-------------|

EN 388



| | |
|------------------------|---------|
| * Abrasion resistance | Level 4 |
| * Blade cut resistance | Level 1 |
| * Tear resistance | Level 2 |
| * Puncture resistance | Level 1 |
| * TDM cut resistance | X |

| Protection against Micro-organisms risk | Performance |
|---|-------------|
|---|-------------|

EN ISO 374-5



| | |
|---|------|
| * Protection against bacteria and fungi | Pass |
| * Protection against viruses | n/a |