

Description: Extra light weight bead rolled flock lined natural rubber gloves

- Features & Benefits:
- \* Anatomically shaped for comfort
  - \* Anti-slip pattern for good grip in wet and dry conditions
  - \* Beaded cuff to improve tear resistance during donning and removal and help prevent droplets from travelling beyond the glove length
  - \* Compliant with (EC) No.1935/2004, EU 10/2011 & BFR XXI (Blue, Yellow)
  - \* Improved sensitivity and dexterity
  - \* Ingredients comply with FDA regulations for food contact (Blue only)
  - \* Natural rubber
  - \* Pure cotton lining to absorb perspiration
  - \* Ingredients comply with FDA regulations for food contact (Blue, Green only)



Applications: Agriculture, Chemical Industry, Food Industry, Pharmaceutical, Facility maintenance

Elastomer: Natural rubber

Thickness: 0.38 +/- 0.04 mm

Lining: Flocklined

Former: Diamond

Exterior: Finished smooth

Cuff Types: Bead rolled

Treatments: Chlorinated

Colours: Blue B1, Blue B2, Green G3, Red R5, Yellow Y1

AQL - Critical: 1.5

Major: 4

CE Certification: Conforms to PPE Regulation EU 2016/425 to (Complex Design) Personal Protective Equipment after assessment against standards EN 374-1:2016+A1:2018, EN 374-5:2016, EN 388:2016+A1:2018 and EN ISO 21420:2020

Conforms to: ASTM D4679 of 2021

Physical Dimensions:	Size	Palm	Wrist	Cuff	Length
	6-6.5	191	175	239	300
	7-7.5	200	187	242	300
	8-8.5	209	200	256	300
	9-9.5	226	219	270	300
	XL	242	237	284	300

Circumference in mm, +/- 5 mm      Tol. +/- 10 mm

Shelf Life 3 Years


EN 374-4

#### Protection against Chemical hazards

Performance

Degradation %

EN ISO 374-1/TYPE A



KLMPST

* Methanol (A)	Level 1	22.3
* Sodium hydroxide 40% (K)	Level 6	-26.8
* Sulphuric acid 96% (L)	Level 2	49.8
* Nitric acid 65% (M)	Level 4	24.7
* Acetic acid 99% (N)	Level 1	27.7
* Hydrogen peroxide 30% (P)	Level 4	-16.9
* Hydrofluoric acid 40% (S)	Level 5	X

Note: Printed copies are valid only on the date printed

Printed Date: 28-Nov-2023

Revision:5

Published Date: 28-Nov-2023

**DPL**  
Handling you with care

No: 400, Deans Road, Colombo 10, Sri Lanka

Phone: +94-0122-683-964

Fax: +94-0122-699-018

E-Mail: postmast@dplgroup.com

\* Formaldehyde 37% (T) Level 6 -16.5

**Protection against Mechanical hazards** Performance



* Abrasion resistance	Level 1
* Blade cut resistance	Level 0
* Tear resistance	Level 1
* Puncture resistance	Level 0
* TDM cut resistance	X

**Protection against Micro-organisms risk** Performance



* Protection against bacteria and fungi	Pass
* Protection against viruses	n/a