

Description: Chlorinated medium weight flock lined natural rubber gloves

- Features & Benefits:
- * Natural rubber
 - * Anatomically shaped for comfort
 - * Pure cotton lining to absorb perspiration
 - * Anti-slip pattern for good grip in wet and dry conditions
 - * Beaded cuff to improve tear resistance during donning and removal and help prevent droplets from travelling beyond the glove length
 - * Low in soluble proteins
 - * Bacteriostatic and fungistatic additives
 - * Compliant with (EC) No.1935/2004, EU 10/2011 & BFR XXI (Blue,Pink,Yellow)
 - * Ingredients comply with FDA regulations for food contact (Blue ,Yellow Y2)

Applications: Agriculture, Chemical Industry, Food Industry, Pharmaceutical, Facility maintenance

Elastomer: Natural rubber

Thickness: 0.52 +/- 0.05 mm

Lining: Flocklined

Former: Diamond, CID

Exterior: Finished smooth

Cuff Types: Bead rolled

Treatments: Chlorinated

Colours: Blue B2, Pink P2, Yellow Y1, Yellow Y2

AQL - Critical: 1.5

Major: 4

CE Certification: Conforms to PPE Regulation EU 2016/425 to(Complex Design) Personal Protective Equipment after assessment against standards EN 374-1:2016+A1:2018, EN 388:2016+A1:2018 ,EN 374-5 : 2016 and EN ISO 21420:2020

Conforms to:

Physical Dimensions:	Size	Palm	Wrist	Cuff	Length
	6-6.5	191	175	239	300
	7-7.5	200	187	242	300
	8-8.5	209	200	256	300
	9-9.5	226	219	270	300
	XL	242	237	284	300
		Circumference in mm, +/- 5 mm		Tol. +/- 10 mm	

Shelf Life 3 Years

Protection against Chemical hazards

Performance

Degradation %

EN ISO 374-1/TYPE A



* Methanol (A)	Level 1	16.8
* Sodium hydroxide 40% (K)	Level 6	14.6
* Sulphuric acid 96% (L)	Level 2	36.4
* Nitric acid 65% (M)	Level 5	4.8
* Acetic acid 99% (N)	Level 2	28.5
* Ammonium hydroxide 25% (O)	Level 1	-0.1
* Hydrogen peroxide 30% (P)	Level 6	31.1
* Formaldehyde 37% (T)	Level 6	17.3

Note: Printed copies are valid only on the date printed

Printed Date: 29-Nov-2023

Revision:3

Published Date: 29-Nov-2023



No: 400, Deans Road, Colombo 10, Sri Lanka

Phone: +94-0122-683-964

Fax: +94-0122-699-018

E-Mail: postmast@dplgroup.com

* Hydrofluoric acid 40% (S)

Level 6

X

Protection against Mechanical hazards

Performance

EN 388



- * Abrasion resistance
- * Blade cut resistance
- * Tear resistance
- * Puncture resistance
- * TDM cut resistance

Level 1
Level 0
Level 1
Level 0
X

Protection against Micro-organisms risk

Performance

EN ISO 374-5



- * Protection against bacteria and fungi
- * Protection against viruses

Pass
Pass