

Description: Chlorinated medium heavy weight flock lined natural rubber gloves

- Features & Benefits:
- \* Heavyduty for added protection
  - \* Anatomically shaped for comfort
  - \* Pure cotton lining to absorb perspiration
  - \* Anti-slip pattern for good grip in wet and dry conditions
  - \* Straight cuff
  - \* Compliant with (EC) No. 1935/2004 & EU 10/2011 (Orange)
  - \* Bacteriostatic and fungistatice additives (optional)
  - \* chlorinated for low extractable proteins

Applications: Agriculture, Chemical Industry, Construction, Food Industry, Facility maintenance



- Elastomer: Natural rubber  
 Thickness: 0.70 +/- 0.07 mm  
 Lining: Flocklined  
 Former: Honeycomb CIH  
 Exterior: Finished smooth  
 Cuff Types: Straight  
 Treatments: Un-chlorinated, Chlorinated  
 Colours: Black D1, Orange O1  
 AQL - Critical: 1.5  
 Major: 4

CE Certification: Conforms to PPE Regulation EU 2016/425 to(Complex Design) Personal Protective Equipment after assessment against standards EN 374-1:2016+A1:2018, EN 374-5:2016,EN 388:2016+A1:2018 and EN ISO 21420:2020

Conforms to:

Physical Dimensions:	Size	Palm	Wrist	Cuff	Length
	6-6.5	198	183	248	300
	7-7.5	208	190	251	300
	8-8.5	215	202	268	300
	9-9.5	235	226	280	300
	XL	250	237	293	310
	XXL	262	248	306	310

Circumference in mm, +/- 5 mm      Tol. +/- 10 mm

Shelf Life 3 Years

#### Protection against Chemical hazards

Performance

Degradation %

EN 374



* Methanol (A)	Level 2	-6.3
* Sodium hydroxide 40% (K)	Level 6	-3.0
* Sulphuric acid 96% (L)	Level 4	27.6
* Nitric acid 65% (M)	Level 6	10.3
* Acetic acid 99% (N)	Level 2	19.9
* Ammonium hydroxide 25% (O)	Level 1	-25.4
* Hydrogen peroxide 30% (P)	Level 6	6.4
* Hydrofluoric acid 40% (S)	Level 6	X
* Formaldehyde 37% (T)	Level 6	-9.2

Note: Printed copies are valid only on the date printed

Printed Date: 29-Nov-2023

Revision:9

Published Date: 29-Nov-2023



No: 400, Deans Road, Colombo 10, Sri Lanka

Phone: +94-0122-683-964


Fax: +94-0122-699-018

E-Mail: postmast@dplgroup.com

**Protection against Mechanical hazards** **Performance**

EN 388 	<ul style="list-style-type: none"><li>* Abrasion resistance</li><li>* Blade cut resistance</li><li>* Tear resistance</li><li>* Puncture resistance</li><li>* TDM cut resistance</li></ul>	<p>Level 2</p> <p>Level 0</p> <p>Level 2</p> <p>Level 0</p> <p>X</p>
---	---	--

**Protection against Micro-organisms risk** **Performance**

EN ISO 374-5 	<ul style="list-style-type: none"><li>* Protection against bacteria and fungi</li><li>* Protection against viruses</li></ul>	<p>Pass</p> <p>Pass</p>
---	--	-------------------------

